


SPECIFICATIONS

GRANDSTAND® SERIES	74534 36" Deck 74536 40" Deck	74578 48" Deck 74549 52" Deck	74553 60" Deck	74588 48" Deck EFI 74589 52" Deck EFI 74583 60" Deck EFI
Engine* at 3600 RPM	15 hp Kawasaki® FS 603cc	22 hp Kawasaki FS 726cc (48") 23 hp Kawasaki FS 726cc (52")	24 hp Kawasaki FS 726cc	23 hp Kohler® Command EFI 747cc (48", 52") 25 hp Kohler® Command EFI 747cc (60")
Electric Start	Standard			
Air Cleaner	Standard			HD Cannister
Drive Tires	18" x 8.5" - 8" (36") 18" x 9.5" - 8" (40")	20" x 10.5" - 8"		
Caster Tires	11" x 4" - 5" flat-free semi-pneumatic			
Fuel Capacity	7.8 gallons		12.0 gallons	7.8 gallons
Fuel Gauge	Standard			
Digital Hour Meter	Standard			
Hydraulic Drive System	Twin pumps & wheel motors			
Max Ground Speed (Fwd)	8.0 mph			
Deck Widths	36" / 40"	48" / 52"	60"	48" / 52" / 60"
Cutting Deck	TURBO FORCE®			
Deck Depth	5.0"	5.5"		
Deck Construction	7-gauge, high-strength steel			
Bull-nose Bumper	Standard			
Adjustable Discharge Baffle	Standard			
Rubber Discharge Chute	Standard			
1" Heavy-Duty Spindle Shaft	Standard			
Spindle Bearings	Ball Bearings			
Tool-Free Height-of-Cut	Standard			
Cutting Height	1.0" - 5.0"			



TURBO FORCE® DECKS

The fabricated deck shell of the TURBO FORCE deck is constructed of 7-gauge, high-strength steel that's 33% thicker and 32% higher in yield strength than ordinary 10-gauge commercial steel used in 7/10 decks. The combined effect is a deck shell that is 75% stronger, so it easily handles the most demanding conditions and resists damage from impacts and abrasion. The deck is further reinforced by the bull-nose front bumper, a ½" trim side wear guard, and a 3/8" thick plate around the discharge opening.



OUTSTANDING FIT

STREAMLINED DESIGN

The GrandStand conserves space to get more machines on your trailer, or allows for a smaller trailer and lighter load. The foldable platform makes it even more compact for transport or storage.

PROPERTY OWNER ACCEPTANCE

Some property owners have negative reactions to larger, heavier-looking mowers and are concerned that their lawns may be damaged. The sleeker Toro GrandStand helps to overcome that problem.

OUTSTANDING PERFORMANCE

VISIBILITY

The exceptional visibility from the GrandStand protects the operator, the mower and the property. The operator is better able to steer clear of obstacles, and easily pass beneath branches.

EFI – SUPERIOR FUEL ECONOMY

- Up to 25% better fuel economy than equivalent carbureted engines
- Lower operating cost
- Easy, no choke starting
- Reduced carbon footprint

Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

490-8742 ©2014 The Toro Company. All rights reserved. * The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAEJ2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.